



### DIMENSIONS (mm)

| a    | b    | c    | d   | e    | f        | g   |
|------|------|------|-----|------|----------|-----|
| 3380 | 1155 | 1570 | 460 | 2330 | 980/1300 | 395 |

|                              |   |
|------------------------------|---|
| Engine                       | Yanmar 3TNV70   |
| N° cylinders / displacement  | 3 / 845 cc  |
| Rated output                 | 14,2 HP at 2300 rpm (10,5 kW / 2300 min <sup>-1</sup> ) |
| Machine weight with canopy   | 1615 / 1675 kg (rubber shoe / steel shoe)               |
| Operating weight with canopy | 1710 / 1770 kg (rubber shoe / steel shoe)               |
| Maximum digging depth        | 2350 mm   |
| Minimum front turning radius | 1580 mm   |
| Max. bucket digging force    | 1600 kgf  |
| STD. Bucket width            | 400 mm  |
| STD. Bucket capacity         | 0,044 m <sup>3</sup>                                    |

### Where others cannot reach

The mini-excavator 17VXE, the new ultra-compact model, utilizes the technology of higher class machines. Power and speed of digging are assured when working in confined spaces: in small restructuring work, in excavations and in maintenance of sewerage systems, in tunnels where larger machines cannot operate, but also in the gardening and nursery sectors.

